

(19)



JAPANESE PATENT OFFICE

PATENT ABSTRACTS OF JAPAN

(11) Publication number: **08202857 A**

(43) Date of publication of application: **09.08.96**

(51) Int. Cl.

**G06T 1/00**  
**G06T 11/80**

(21) Application number: **07012323**

(22) Date of filing: **30.01.95**

(71) Applicant: **CANON INC**

(72) Inventor: **SAKAGUCHI KATSUHIKO**  
**ARAI TSUNEICHI**  
**MORI SHIGEKI**  
**HARADA TAKASHI**  
**MATSUBAYASHI KAZUHIRO**

(54) PLOTTING DEVICE

processing is terminated.

(57) Abstract:

COPYRIGHT: (C)1996,JPO

PURPOSE: To easily set a plotting attribute so as to display a drawing at the time of setting color information of a plotting point by indicating and inputting the display coordinate and the color of the drawing displayed on a display means by a coordinate indication means.

CONSTITUTION: A plotting device consists of a coordinate input device 1, a display device 2, data RAM 3 and CPU 4. The coordinate device 1 is a pen input device giving an indication on a tablet by a pen. The display device 2 can display the gray scales of eight colors in a pixel units. RAM 3 is RAM storing attribute information corresponding to color information and stores a flag discriminating the thickness of the pen and whether a line is a dotted line or a solid line. When an icon is depressed by the pen, the next pen is depressed more than tab and the last coordinate which is penned up is inputted. Then, a color table stored in data RAM 3 is retrieved and information on thickness and a type, which correspond to the color concerned, is read. Attribute information which is read is set to be attribute information on the present pen and a

